MULTI-OBJECTIVE OPTIMIZATION OF PROTON EXCHANGE MEMBRANE FUEL CELL SYSTEMS USING FUZZY LOGIC CONTROLLER: A REVIEW

Zirata, K.B., Thuku, I.T., Ibrahim, V.M.* and Patrick, D.O.

Department of Electrical/Electronic Engineering, Modibbo Adama University, Yola, Nigeria

*Corresponding email: visaibrahim@gmail.com

ABSTRACT

Proton Exchange Membrane Fuel Cell, being non-linear in nature, possess great control problems to linear controllers such as particle swarm optimization, especially when variable operating conditions are desired. Optimizing PEMFC performance requires balancing multiple conflicting objectives, including efficiency, cost, durability, power output, and operational stability. This paper reviews multi-objective optimization techniques for the purpose of integrating Fuzzy Logic Controller in the multi-objective optimization of PEMFC systems to overcoming the inherent challenges of PEMFC technology (complex, nonlinear, and multi-variable nature). Multi-objective optimization (MOO) techniques are employed to address these challenges, with fuzzy logic-based controller (FLC) emerging as a powerful approach due to its ability to handle uncertainty and nonlinear system dynamics. Fuzzy Logic Based-Particle Swarm Optimization (FL-PSO) offers a powerful approach for optimizing PEMFC systems by dynamically adjusting operating parameters for higher efficiency, longer durability, and lower costs. Its ability to handle uncertainty and multi-objective trade-offs makes it a promising tool for the next generation of fuel cell technology.

Keywords: Proton Exchange Membrane Fuel Cell, Multi-Objective Optimization, Fuzzy Logic Controller, Particle Swarm Optimization, Genetic Algorithm, Hybrid Optimization

1 INTRODUCTION

Proton Exchange Membrane Fuel Cell (PEMFC) is an electrochemical device that converts chemical energy from hydrogen and oxygen into electricity, using a proton-conducting membrane [1]. It is an emerging technology in the field of renewable energy, known for their high efficiency and low emissions. They operate by converting chemical energy from hydrogen into electrical energy, with water as the only by-product [2] It consists of an anode, a cathode, and a proton-conducting membrane [1]. Hydrogen is fed into the anode, where it splits into protons and electrons. The protons pass through the membrane to the cathode, while the electrons travel through an external circuit, generating electricity. At the cathode, the protons, electrons, and oxygen combine to form water. This process is efficient and environmentally friendly, making PEMFCs suitable for various applications, including transportation, stationary power generation, and portable power devices. This technology is considered crucial for addressing the global need for clean and sustainable energy sources. However, optimizing the performance of PEMFC systems is challenging due to their complex, nonlinear, and multi-variable nature [3]. Despite their advantages, PEMFCs face several challenges: Achieving high efficiency requires precise control over operating conditions such as temperature, pressure, and humidity. Traditional optimization methods, such as Particle Swarm Optimization (PSO), have been used for PEMFC optimization [4] Particle Swarm Optimization is a population-based optimization technique inspired by the social behavior of birds flocking or fish schooling. Each particle represents a potential solution and adjusts its position based on personal experience and the experience of neighboring particles. Multi-objective PSO can effectively find a diverse

set of Pareto optimal solutions [5] The method often falls short due to the complexity of the systems involved [4]. However, this method can struggle with the complex, nonlinear relationships and interactions within PEMFC systems. This is where advanced control strategies like Fuzzy Logic Controller (FLC) come into play [6, 7]. Fuzzy logic is a form of many-valued logic that deals with approximate reasoning rather than fixed and exact reasoning. It is particularly useful for systems that are difficult to model mathematically, such as PEMFCs. FLC use a set of rules and membership functions to mimic human reasoning and decision-making processes [8] The advantages of using FLC for PEMFC optimization include: Robustness, handling uncertainties and variations in system parameters better than traditional controllers. Flexibility can easily be modified and adapted to different operating conditions; Simplicity can be designed without needing an exact mathematical model of the system. The integration of Fuzzy Logic Controller in the multi-objective optimization of PEMFC systems represents a promising approach to overcoming the inherent challenges of PEMFC technology (complex, nonlinear, and multi-variable nature).

2 OPERATION OF PEMFCS

Hydrogen gas is supplied to the anode, while oxygen (usually from the air) is supplied to the cathode. The gases are distributed through the flow channels in the bipolar plates to the respective electrodes. At the anode, hydrogen molecules are split into protons and electrons. The protons migrate through the PEM to the cathode, while the electrons travel through the external circuit, creating an electric current. Water is produced at the cathode during the electrochemical reaction. Effective water management is crucial to prevent flooding of the electrodes and to maintain membrane hydration for optimal proton conductivity. Additionally, heat generated during the reaction must be managed to maintain the desired operating temperature and ensure system stability. The electrons traveling through the external circuit generate an electric current, which can be harnessed to power external devices. The overall cell voltage is the difference between the anode and cathode potentials, and the power output is a product of this voltage and the current [9]. The general working principle of PEMFC has been demonstrated in Figure 1 [10]. The PEMFC operates through the following steps: (i) Hydrogen Oxidation at the Anode: $H_2 \rightarrow 2H^+ + 2e^-$. Hydrogen molecules split into protons and electrons at the anode catalyst layer, (ii) Proton Transport through the Membrane: The proton exchange membrane allows only hydrogen ions (H^+) to pass through to the cathode while blocking electrons. (iii) Electron Flow through an External Circuit: The freed electrons travel through an external electrical circuit, generating an electric current. (iv) Oxygen Reduction at the Cathode: $1/2O_2 + 2H^+ + 2e^- \rightarrow H_2O$. Oxygen molecules combine with protons and electrons to form water, the only byproduct.



Figure 1. Working principle of PEMFC [10]

2.1 Performance Considerations

Efficiency: The efficiency of PEMFCs is influenced by factors such as the type and thickness of the membrane, the catalyst loading, and the operating conditions (temperature, pressure, and humidity). Durability: Durability is affected by the degradation of the membrane and catalyst, often caused by factors such as chemical attack, mechanical stresses, and contamination from impurities in the fuel or air. Dynamic Response: PEMFCs must respond quickly to changes in load demand, particularly in automotive applications. This requires careful control of the fuel and air supply, as well as effective thermal and water management [11].

2.2 Advantages and Challenges

Advantages: PEMFCs offer high power density, low operating temperature, and rapid startup. They produce only water as a byproduct, making them environmentally friendly. Despite its advantages, PEMFC faces several challenges that require optimization. Challenges: Challenges include the high cost of platinum catalysts, durability issues related to membrane and catalyst degradation, enhancing hydrogen and oxygen utilization to maximize efficiency and the need for efficient water and thermal management systems [12, 13] . Optimization techniques, including fuzzy logic-based approaches, play a crucial role in addressing these challenges and improving the overall performance of PEMFC systems.

3 MULTI-OBJECTIVE OPTIMIZATIONS IN PEMFC SYSTEMS

Multi-objective optimization involves simultaneously optimizing two or more conflicting objectives subject to certain constraints [14]. In the context of Proton Exchange Membrane Fuel Cell (PEMFC) systems, multi-objective optimization is crucial for balancing various performance criteria such as efficiency, durability, cost, and environmental impact [15]. This section explores the principles of multi-objective optimization, common techniques, and their applications in energy systems. The primary objectives in PEMFC optimization include: Maximizing Efficiency: Higher energy conversion efficiency ensures better fuel utilization and lower operational costs. Maximizing Durability: Enhancing the lifespan of the fuel cell by reducing degradation mechanisms in the catalyst and membrane. Minimizing Cost: Reducing material and manufacturing costs while maintaining performance standards. Maximizing Power Output: Ensuring the PEMFC delivers sufficient power for its intended application whether in transportation, stationary or portable energy systems.

3.1 Trade-Offs and Constraints in PEMFC Optimization

Since PEMFC parameters are interdependent, optimizing one objective often negatively impacts others. Key trade-offs include: Efficiency vs. Power Output: Increasing power output may reduce efficiency due to higher current densities causing more losses. Durability vs. Cost: Using high-quality materials (e.g., platinum-based catalysts) increases durability but raises costs. Water and Thermal Management Trade-offs: Maintaining membrane hydration without flooding is challenging, requiring an optimal balance between humidification and heat dissipation. Typical constraints in PEMFC optimization include: Voltage Range: 0.6V – 1.2V per cell to ensure stable operation; Current Range: 10A – 200A, depending on the application; Efficiency Threshold: ≥40% for practical energy conversion; Cost Limit: $200–500 per kW for economic viability; Durability Requirement: ≥5000 hours of operation.

3.2 Multi-objective Optimization Techniques

Multi-objective optimization involves simultaneously optimizing two or more conflicting objectives subject to certain constraints [14]. In the context of Proton Exchange Membrane Fuel Cell (PEMFC) systems, multi-objective optimization is crucial for balancing various performance criteria such as efficiency, durability, cost, and environmental impact [15].

3.2.1 Common Multi-objective Optimization Techniques

Genetic Algorithms (GAs): Genetic algorithms are inspired by the principles of natural selection and genetics. They use a population of potential solutions that evolve over generations to find optimal

solutions [16]. Multi-objective GAs, such as NSGA-II (Non-dominated Sorting Genetic Algorithm II), are widely used due to their ability to handle complex, non-linear problems and maintain diversity in the solution set. Genetic Algorithm (GA): Mimics natural selection to explore multiple solutions but may require high computational time. Genetic algorithms are Inspired by natural selection; it evolves potential solutions through selection, crossover, and mutation; and Well-suited for multi-objective optimization but computationally intensive.

Particle Swarm Optimization (PSO): Particle Swarm Optimization is a population-based optimization technique inspired by the social behavior of birds flocking or fish schooling. Each particle represents a potential solution and adjusts its position based on personal experience and the experience of neighboring particles. Multi-objective PSO can effectively find a diverse set of Pareto optimal solutions [5]; [17] . Particle Swarm Optimization (PSO), inspired by swarm intelligence, offering fast convergence but may get trapped in local optima. Based on swarm intelligence, PSO updates particle positions based on their own experience and the global best solution; Provides fast convergence but may get trapped in local optima.

Ant Colony Optimization (ACO): Ant Colony Optimization is inspired by the foraging behavior of ants. It uses a colony of artificial ants to explore the search space and find optimal paths [18]. Multi-objective ACO algorithms are used to solve complex optimization problems by mimicking the way ants prioritize different objectives while finding food sources. Ant Colony Optimization Mimics the foraging behavior of ants to find optimal paths; is Effective for path optimization in fuel delivery systems but computationally expensive for complex PEMFC problems.

Simulated Annealing (SA): Simulated Annealing is a probabilistic optimization technique inspired by the annealing process in metallurgy. It explores the solution space by accepting both better and worse solutions with a certain probability to avoid local optima [19]. Multi-objective SA can handle multiple conflicting objectives by incorporating a Pareto-based acceptance criterion. Simulated Annealing is Inspired by annealing in metallurgy, SA probabilistically accepts worse solutions to escape local minima; Useful for global optimization but requires careful tuning of cooling parameters.

Multi-objective Differential Evolution (MODE): Differential Evolution is an evolutionary algorithm that optimizes problems by iteratively improving candidate solutions. Multi-objective Differential Evolution extends this concept to handle multiple objectives, maintaining a diverse set of solutions and efficiently converging to the Pareto front [20].

Evolutionary Multi-objective Optimization (EMO): EMO encompasses a broad class of algorithms that use evolutionary principles to solve multi-objective optimization problems. These algorithms maintain a population of solutions and apply selection, crossover, and mutation operations to evolve towards the Pareto front [21].

Hybrid Optimization Approaches (FL-PSO, FL-GA): Combining fuzzy logic (FL) with PSO or GA enhances decision-making under uncertainty. To overcome the limitations of individual techniques, hybrid approaches combine different algorithms for improved performance.

3.3 Need for Fuzzy Logic in Multi-Objective Optimization

Traditional optimization techniques struggle with handling the nonlinear and uncertain nature of PEMFC systems [22]. Fuzzy logic [23] provides: Adaptability, Adjusts control parameters dynamically; Robustness, Handles imprecise and incomplete data effectively; Better Trade-Off Management, Finds optimal balance between competing objectives without requiring an exact mathematical model.

3.4 Fuzzy Logic-Based Particle Swarm Optimization (FL-PSO)

Fuzzy Logic-Based Particle Swarm Optimization (FL-PSO) is an advanced optimization technique that integrates fuzzy logic (FL) with particle swarm optimization (PSO) to enhance decision-making and optimization in complex, uncertain environments [24, 25]. This hybrid approach is particularly useful for

applications like Proton Exchange Membrane Fuel Cell (PEMFC) systems, where multiple conflicting objectives (e.g., efficiency, durability, and cost) need to be optimized under varying operating conditions. Fuzzy logic is used to dynamically adjust PSO parameters (e.g., inertia weight, cognitive and social coefficients) based on system conditions. This allows PSO to handle uncertainty and nonlinear relationships more effectively. Instead of using fixed parameter values, FL adapts these values in real-time, making the optimization process more adaptive and efficient. The integration of fuzzy logic into MOO frameworks significantly enhances the optimization process [26], leading to improved efficiency, durability, and cost-effectiveness in PEMFC systems as can be seen in Table 1.

Table 1. Comparative Analysis of Optimization Techniques

Method	Adavantages	Disadvantages
Gradient-based method	Fast for smooth functions	Poor performance on non-smooth functions
GA	Effective for global optimization	High computational cost
PSO	Fast convergence	May get stuck in local optima
SA	Avoids local optima	Slow convergence
ACO	Good for path finding	Computationally intensive
FL-PSO / FL-GA	Handles uncertainty well	Requires fine-tuning of fuzzy rules

4 CONCLUSIONS

Fuzzy logic has emerged as a powerful tool for multi-objective optimization in PEMFC systems. Its ability to handle uncertainty, adapt to changing conditions, and optimize multiple conflicting objectives simultaneously makes it an ideal solution for improving PEMFC performance. By integrating fuzzy logic with advanced metaheuristic algorithms such as PSO and GA, significant improvements in efficiency, durability, and cost-effectiveness can be achieved. Fuzzy Logic-Based PSO (FL-PSO) is an effective method for optimizing PEMFC systems by dynamically adjusting parameters based on real-time system behavior. Its ability to balance exploration and exploitation makes it superior to conventional PSO, leading to better efficiency, durability, and cost-effectiveness in fuel cell applications. FL-PSO offers a powerful approach for optimizing PEMFC systems by dynamically adjusting operating parameters for higher efficiency, longer durability, and lower costs. Its ability to handle uncertainty and multi-objective trade-offs makes it a promising tool for the next generation of fuel cell technology. To overcome the limitations of individual techniques, hybrid approaches combine different algorithms for improved performance.

REFERENCES

1. Pain, P. and Dewan, D. (2020). Concept of Hydrogen Fuel Cell Technology. *Int. Res. J. Eng. Technol.*, vol. 7, no. 1, pp. 1007-1012.

2. Min, T., Zhang, R., Chen, L. and Zhou, Q. (2023). Reactive Transport Processes in Proton Exchange Membrane Fuel Cells. *Encyclopedia*, vol. 3, no. 1, pp. 746-758.

3. Aly, M., Mohamed, E.A., Rezk, H., Nassef, A.M., Elhosseini, M.A. and Shawky, A. (2023). An Improved Optimally Designed Fuzzy Logic-Based MPPT Method for Maximizing Energy Extraction of PEMFC in Green Buildings. *Energies*, vol. 16, no. 1197.

4. Sakai, A., Christopher, R.D., Frank, H.T.N., Aafke, J.J., Daniela, M.C.B., Christopher, P.K., Kim, S.W., Hans, A.H., Wilhelm, T.S.H., Katarzyna, P.A. and John, I.G. (2022). Traditional protocols and optimization methods lead to absent expression in a mycoplasma cell-free gene expression platform. *Synthentic Biol.*, vol. 7, no. 1, pp. 1-14.

5. Li, Y., Ma, Z., Zheng, M., Li, D., Lu, Z. and Xu, B. (2021). Performance Analysis and Optimization of a High-Temperature PEMFC Vehicle Based on Particle Swarm Optimization Algorithm. *Membranes (Basel)*, vol. 11, no. 691, pp. 1-16.

6. Abdolrasol, M.G.M., Ayob, A., Hussein, A. and Selim, T. (2023). Optimal fuzzy logic controller based PSO for photovoltaic system. *Energy Reports*, vol. 9, no. 2023, pp. 427-434.

7. Ruan, Z., Wu, H., Wang, R., Tian, Z. and Li, W. (2024). Particle swarm optimization Fuzzy algorithm applied to temperature control in PEM fuel cell systems. *Energy proceedings*, vol. 45, pp. 1-7.
8. Lee, S. and Kim, J. (2024). Data-Driven Adaptive Fuzzy Systems for PEMFC Longevity Enhancement. *Fuel Cells Bull.*, vol. 2024, no. 4, pp. 12-19.
9. Habib, M.S., Salam, M.A., Ahmed, K., Uddin, M.S., Hossain, T., Papri, N., Islam, T. and Arefin, P. (2021). Proton Exchange Membrane Fuel Cell (PEMFC) Durability Factors, Challenges and Future Perspectives : A Detailed Review. *Mater. Sci. Res. India*, vol. 18, no. 2, pp. 217-234.
10. Liu, Z., Liu, L. and Zhou, Y. (2022). Modelling and simulation analysis of closed proton exchange membrane fuel cell system. *Energy Reports*, vol. 8, no. 2022, pp. 162-168.
11. Soomro, I.A., Memon, F.H., Mughal, W., Khan, M.A., Ali, W., Liu, Y., Choi, K.H. and Thebo, K.H. (2023). Influence of Operating and Electrochemical Parameters on PEMFC Performance : A Simulation Study. *Membranes (Basel)*, vol. 13, no. 259, pp. 1-14.
12. Alaswad, A., Omran, A., Sodre, J.R., Wilberforce, T., Pignatelli, G., Dassisti, M., Baroutaji, A. and Olabi, A.G. (2021). Technical and Commercial Challenges of Proton-Exchange Membrane (PEM) Fuel Cells. *Energies*, vol. 14, no. 144, pp. 1-21.
13. Tellez-cruz, M.M., Escorihuela, J. and Solorza-feria, O. (2021). Proton Exchange Membrane Fuel Cells (PEMFCs): Advances and Challenges. *Polymers (Basel)*, vol. 13, no. 18, pp. 1-54.
14. Sharifi, M.R., Akbarifard, S., Qaderi, K. and Madadi, M.R. (2021). OPEN A new optimization algorithm to solve multi - objective problems. *Sci. Rep.*, vol. 21, no. 20326, pp. 1-19.
15. Wu, G. and Luo, N. (2023). Multi-objective optimization of PEMFC performance based on grey correlation analysis and response surface method. *Front. Energy Res.*, vol. 11:1206418, , pp. 1-14.
16. Polo-mendoza, R., Martinez-arguelles, G. and Peñabaena, R. (2023). A multi-objective optimization based on genetic algorithms for the sustainable design of Warm Mix Asphalt (WMA). *Int. J. Pavement Eng.*, vol. 24, no. 2, pp. 1-22.
17. Hussin, M. and Talib, A. (2019). Fuzzy logic with a novel advanced firefly algorithm and sensitivity analysis for semi-active suspension system using magneto-rheological damper," *J. Ambient Intell. Humaniz. Comput.*, vol. 10, no. 8, pp. 3263-3278.
18. Duan, H. (2011). Ant Colony Optimization : Principle, Convergence. *Handbook of Swarm Intelligence*, pp. 373-374.
19. Delahaye, D., Chaimatanan, S. and Mongeau, M. (2019). Simulated annealing : From basics to applications To cite this version : HAL Id : hal-01887543 Simulated Annealing : From Basics to Applications. *Handbook of Metaheuristics*, pp. 1-44.
20. Fan, M., Chen, J., Xie, Z., Ouyang, H., Li, S. and Gao, L. (2022). Improved multi - objective differential evolution algorithm based on a decomposition strategy for multi-objective optimization problems. *Sci. Rep.*, vol. 12, no. 21176, pp. 1-14.
21. Baumann, J. and Kramer, O. (2024). Evolutionary Multi-Objective Optimization of Sentiments. *Comput. Intell. Lab*, pp. 1-14.
22. Kumar, D. (2012). Traditional vs. non-traditional optimization tools. *Traditional vs. non-traditional optimization tools*, pp. 1-6.
23. Saatchi, R. (2024). Fuzzy Logic Concepts , Developments and Implementation. *Information*, vol. 15, no. 656, pp. 1-24.
24. Chakraborty, D., Guha, D. and Dutta, B. (2015). Multi-objective optimization problem under fuzzy

rule constraints using particle swarm optimization. S*oft Comput.*, vol. 20, no. 6, pp. 1-15.

25. Omakor, J. and Alzayed, M. (2024). Particle Swarm-Optimized Fuzzy Logic Energy Management of Hybrid Energy Storage in Electric Vehicles. *Energies*, vol. 17, no. 2163.

26. Morri, N., Hadouaj, S. and Ben Said, L. (2022). Fuzzy logic based multi-objective optimization of a multi-agent transit control system, *Memetic Comput.*, vol. 15, no. 2, pp. 1-17.